

Proudfoot Company, Inc

588 Pepper Street

Monroe, CT, 06468, US

Phone: 203.459.0031

Fax: 203-459-0033

Toll-free: 800.445.0034

Email: Info@TheProudfootCompany.com

Website: <http://www.tbeproudfootcompany.com>

Item # A-2, A-2 Quilted Fiberglass Absorber

A-2 Quilted Fiberglass Absorber



Quilted Fiberglass Absorbers reduce the reflection of sound waves by adding soft, porous, open-celled materials to any environment. Noisemaster's A-2 consists of a vinyl-coated-fiberglass-cloth facing on both sides of two-inch thick quilted fiberglass. Wall panels and overhead baffles are constructed with all edges bound and grommets across the top. Rolls are available 4' wide x 25' long and can be supplied with edges bound or unbound.

- Class A (or 1) Flammability Rated per ASTM E84
 - NRC rating 0.85
 - Available colors: gray, white, black, or tan
 - Straight-stitch or diamond quilt patterns
- Vinyl coated fiberglass cloth facing / fiberglass batt / vinyl coated fiberglass cloth facing

SPECIFICATIONS

Nominal Thickness	2.0 in
Temperature Range	-20 to 180 °F
Standard Width	48 in
Roll Length	25 ft
Flammability	Flame Spread: 17.66 Smoke Density: 22.75
Available Facing Color	Black Gray Tan White
Weight	0.45 lbs/ft ²
Applications	Typically used when you are trying to reduce the reflection of sound waves or reverberant noise energy within a piece of equipment, a room, or a building. Also used to supplement plywood structures on job sites to improve the transmission loss of the wood