

Proudfoot Company, Inc

588 Pepper Street

Monroe, CT, 06468, US

Phone: 203.459.0031

Fax: 203-459-0033

Toll-free: 800.445.0034

Email: Info@TheProudfootCompany.com

Website: <http://www.tbeproudfootcompany.com>

Item # ABA-1, ABA-1 Noise Barrier/Sound Absorber Composite



ABA-1 Noise Barrier/Sound Absorber Composite

The barrier septum configuration offers the benefits of both sound absorption and noise barriers. Noisemaster's ABA-1 consists of a non-reinforced 1-lb psf loaded vinyl noise barrier sandwiched between two layers of vinyl-coated-fiberglass-cloth faced 1" quilted fiberglass sound absorbers.

- Curtain panels with grommets across the top and hook and loop fasteners along the vertical edges
- Rolls are available 4' wide x 25' long and can be supplied with edges bound or unbound
- Available colors: gray, white, black, or tan
- Class A (or 1) flammability rated per ASTM E84

Vinyl coated fiberglass cloth faced 1" quilted fiberglass / 1lb-psf non-reinforced loaded vinyl barrier/ Vinyl coated fiberglass cloth faced 1" quilted fiberglass

SPECIFICATIONS

Nominal Thickness	2.0 in
Temperature Range	-20 to 180 °F
Standard Width	48 in
Roll Length	25 ft
Flammability	Flame Spread: 22.78 Smoke Density: 30.56
Available Facing Color	Black Gray Tan White
Weight	1.5 lbs/ft ²
Applications	Typical uses include curtain panels in acoustical curtain enclosures. Also used as separator walls or divider partitions between noise sources. Commonly used to line the perimeter walls of a building, or as a free-hanging noise barrier/sound absorber wall